

Additional Resources: Product Page

date 09/11/2024

page 1 of 4

MODEL: CMS-2812-078T | DESCRIPTION: SPEAKER

FEATURES

- 8 ohm
- 0.78 W
- through hole






SPECIFICATIONS

parameter	conditions/description	min	typ	max	units
input power	max power: 1 minute on, 2 minutes off, 10 cycles		0.78	1.5	W
impedance	at 1.0 kHz, 1 V	6.8	8	9.2	Ω
resonant frequency (Fo)	at 1 V	400	500	600	Hz
frequency response		Fo		20,000	Hz
sound pressure level	at 0.5 kHz, 0.78 W, 50 cm at 1.0 kHz, 0.78 W, 50 cm at 2.0 kHz, 0.78 W, 50 cm at 3.0 kHz, 0.78 W, 50 cm	78 78 77 79	81 81 80 82	84 84 83 85	dB dB dB dB
distortion	at 1.0 kHz, 3.3 V			11	%
ouzz, rattle, etc.	must be normal at sine wave between 300 Hz ~ 5 kHz			2.5	V
polarity	cone moves forward w/ positive dc current to "+" terminal				
dimensions	Ø28 x 12.5				mm
magnet	Nd-Fe-B				
housing material	MPPO				
cone material	PEI				
terminal	pins				
weight			8.8		g
operating temperature		-40		85	°C
storage temperature		-40		85	°C
RoHS	yes		<u> </u>		

Notes: $1. \ All \ specifications \ measured \ at \ 15~35°C, \ humidity \ at \ 45~85\%, \ under \ 86~106 \ kPa \ pressure, \ unless \ otherwise \ noted.$

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
hand soldering	for 3~5 seconds	370	380	390	°C
wave soldering	see recommended wave soldering profile	,		250	°C



MECHANICAL DRAWING

units: mm tolerance: ±0.3 mm

12.5±0.2

10.2


Pads

Hole

Recommended PCB Layout

Top View


RESPONSE CURVES



Total Harmonic Distortion Curve

Frequency (Hz)

Test Conditions: 0.78 W / 10 cm



Additional Resources: Product Page

SAME SKY | MODEL: CMS-2812-078T | DESCRIPTION: SPEAKER

REVISION HISTORY

rev.	description	date
1.0	initial release	12/07/2023
1.01	CUI Devices rebranded to Same Sky	09/11/2024

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.