Additional Resources: Product Page | <u>3D Model</u>



**date** 09/12/2024 **page** 1 of 3

### MODEL: MJ-63032A | DESCRIPTION: AUDIO JACK

#### FEATURES

- panel mount
- right angle
- 2 conductor
- open housing design
- threaded with nut



.....

## RoHS

#### **SPECIFICATIONS**

parameter	conditions/description	min	typ	max	units
rated input voltage			12		Vdc
rated input current				1	А
contact resistance	between terminal and mating plug			30	mΩ
insulation resistance	at 500 Vdc	100			MΩ
voltage withstand	for 1 minute			500	Vac
insertion/withdrawal force		0.4		3	kg
operating temperature		-25		70	°C
life			5,000		cycles
flammability rating	see material table				
RoHS	YES				

#### SOLDERABILITY


.....


parameter	conditions/description	min	typ	max	units
hand soldering	for 3~5 seconds		360		°C


#### **MECHANICAL DRAWING**



ITEM	DESCRIPTION	MATERIAL	PLATING/COLOR
1	sleeve spring	phosphor bronze	silver
2	tip spring	phosphor bronze	silver
З	housing	PA66 (UL94V-0)	black
4	nut	PA66 (UL94V-0)	black
5	washer	paper	black










.....

Ø7/16"XG20 METRIC THREAD-








Ø6.35 MATING PLUG

.....



#### **REVISION HISTORY**

rev.	rev. description	
1.0	initial release	08/11/2020
1.01	logo, datasheet style update	08/17/2022
1.02	CUI Devices rebranded to Same Sky	09/12/2024

The revision history provided is for informational purposes only and is believed to be accurate.

Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

# same sky

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.