same sky

### SERIES: SF100 | DESCRIPTION: THERMAL PAD

#### **FEATURES**

- 1.5 W/m\*K thermal conductivity
- naturally tacky
- silicone based
- electrical isolation
- sizes to match CUI peltier footprints



## RoHS

#### **SPECIFICATIONS**

parameter	test method/conditions/description	min	typ	max	units
material	silicone elastomer				
color	blue				
thickness	ASTM D751		0.5		mm
specific gravity	ASTM D297		2.2		g/cc
hardness	ASTM D2240	15		80	shore OO
tensile strength	ASTM D412		35		psi
continuous use temperature		-58		200	°C
dielectric breakdown voltage	ASTM D149	2500			V
dielectric constant (1 MHz)	ASTM D150		6.0		÷
volume resistivity	ASTM D257		10 <sup>13</sup>		Ω*cm
thermal conductivity	ASTM D5470		1.5		W/m*K
RoHS	yes				

#### PART NUMBER KEY

.....



Footprint Size (mm): 10x10 = 1010 15x15 = 1515 15x30 = 1530 20x20 = 2020 20x40 = 2040 26.25x50 = 2650 30x12 = 3012 30x30 = 3030 31.25x30 = 3130 40x40 = 4040 41.25x45 = 4145 50x50 = 5050 70x70 = 7070



#### **REVISION HISTORY**

rev.	description	date	
1.0	initial release	11/02/2018	
1.01	brand update	03/23/2020	
1.02	logo, datasheet style update	08/05/2022	
1.03	CUI Devices rebranded to Same Sky	09/12/2024	

The revision history provided is for informational purposes only and is believed to be accurate.

Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

# same sky

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.