Additional Resources: Product Page



date 09/12/2024

page 1 of 4

## MODEL: SJ2-3514A-SMT-TR | DESCRIPTION: AUDIO JACK

#### **FEATURES**

- 4 conductor
- · right angle
- reflow solder compatible
- surface mount





#### **SPECIFICATIONS**


parameter	conditions/description	min	typ	max	units
rated input voltage			12		Vdc
rated input current				1	А
contact resistance	between terminal and mating plug between terminal in a closed circuit			100 30	$m\Omega$
insulation resistance	at 500 Vdc	100			МΩ
voltage withstand	for 1 minute			500	Vac
insertion/withdrawal force		0.3		3	kg
operating temperature		-25		85	°C
life			5,000		cycles
flammability rating	UL94V-D				
RoHS	yes				

#### **SOLDERABILITY**

Note:


parameter	conditions/description	min	typ	max	units
reel storage	≤40°C, ≤80% humidity				
reflow soldering	see reflow profile	255	260		°C

1. Same Sky recommends usage of the product within 24 hours after T&R is opened. After 24 hours, Same Sky recommends drying the parts prior to use.





# **MECHANICAL DRAWING**


units: mm tolerance: X.X ±0.3 mm X.XX ±0.25 mm X.XXX ±0.20 mm PCB: ±0.05 mm unless otherwise specified




DESCRIPTION	MATERIAL	PLATING/COLOR
terminal 1	phosphor bronze	silver
terminal 2	phosphor bronze	silver
terminal 3	phosphor bronze	silver
terminal 4	phosphor bronze	silver
housing	PA9T (UL94V-0)	black









Top View


1432 14 Ø3.5 MATING PLUG

Model No.	SJ2-3514A-SMT-TR
Schematic	01 04 03 03 02
PIN	
1	sleeve
2	tip
3	ring 1
4	ring 2

## **PACKAGING**

units: mm

Reel Size: Ø380 mm Reel QTY: 800 pcs per reel



### **REVISION HISTORY**

rev.	description	date
1.0	initial release	12/12/2016
1.01	added storage and drying conditions	06/22/2017
1.02	brand update	10/10/2019
1.03	product reengineered for improved manufacturability and production yield, see PCN for details	09/27/2023
1.04	CUI Devices rebranded to Same Sky	09/12/2024

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.